OBR ADV Gear Switchback Tank Bag Installation Instructions

Congratulations on your OBR ADV Gear Switchback Tank Bag purchase. Your tank bag has been designed to fit a wide range of motorcycles. Proper installation of your Switchback Tank Bag will ensure secure and safe fitment to your motorcycle.

The OBR ADV Gear Switchback Tank Bag utilizes a three strap system to universally anchor over your motorcycles fuel tank. One (1) forward strap loops forward and under your motorcycles steer head and back up to the two (2) forward SRB buckles on the front of the bag. Make sure that routing of this forward strap is under any wiring or control cables and that the position of the forward strap does not in any way interfere with your control or impede operation of your motorcycle. Included with the forward strap is one (1) elastic tension strap. This elastic tension strap is to be positioned towards the top edge of your tank in front of your fill cap. This tension strap helps maintain a centralized position of the forward strap.

The two (2) straps extending off the rear of the tank bag are meant to attach along your motorcycles frame or sub frame. Actual attachment points for these straps will vary by preference and by motorcycle. It is best to maintain as much of the natural angle of the rear SRB Buckles as possible. This will ensure that adequate downward pull is applied to the rear of the bag for a snug fit. Unthread the webbing of the rear anchor straps from the male SRB and Triglide buckles. Loop the anchor strap through your chosen point and through the square loop at the end of the strap. Reinstall the Triglide and then rethread the webbing back through the male SRB. Adjust tension of the rear anchor straps and pass the webbing back through the Triglide to lock the strap adjustment.

All attachment straps are supplied with extra length. After completion of proper fitment the straps can be trimmed and melted to adjust finish length of the webbing strap tails.





Thank you for your purchase



